



RMT 1230



RMT 1210



RMT 117



RMT 117L



RMT 1240



RMT 37P/P60/P90



RMT 20 PS



RMT 0112



RMT 0112 EXT



RMT RTEX



RMT 1210 SVR



RMT 1260 / 1290



RMT 1260 SVR / 1290 SVR

## PAVING BREAKERS

RMT pneumatic breakers are available in weights, ranging from 35 lb to 90 lb class (20 kg to 41 kg). The hammers are available with different shank size, varying from 25 mm to 32 mm shank (1" to 1¼"). These air tools are capable of light, medium and heavy duty jobs such as demolition, construction, renovation, road construction, bridge work and street repairs. Depending on the job in hand, users will find the most suitable breaker in RMT range. Being considered as the "manufacturer of high quality Paving Breakers from India", all our breakers are manufactured with the goal of providing "Operator's safety, maximum power, maximum durability, easily serviceable and affordable price"



Model #	RMT 1210	RMT 1230	RMT 117	RMT 1240	RMT 117 L	RMT 0112	RMT 0112 EXT	RMT 20 PS	RMT 1210 SVR
Weight with silencer (kg / lb)	20 kg / 44 lb	30 kg / 66 lb	37 kg / 81 lb	40 kg / 88 lb	41 kg / 91 lb	14.5 kg / 32 lb	16 kg / 35 lb	20 kg / 44 lb	24.5 kg / 55 lb
Weight without silencer (kg / lb)	19.4 kg / 42.7 lb	29 kg / 64 lb	36 kg / 80 lb	39 kg / 86 lb	40 kg / 89 lb	13.5 kg / 30 lb	-	-	-
Length (mm / inch)	609 mm / 24"	660 mm / 26"	710 mm / 28"	718 mm / 28.25"	710 mm / 28"	535 mm / 21"	800 mm / 31.5"	635 mm / 25"	600 mm / 24"
Air pressure (bar / psi)	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	7 bar / 102 psi	6 bar / 87 psi
Air consumption (l/s / cfm)	23 l/s / 48 cfm	30 l/s / 65 cfm	35 l/s / 74 cfm	38 l/s / 81 cfm	35 l/s / 74 cfm	23 l/s / 49 cfm	23 l/s / 49 cfm	25 l/s / 53 cfm	26.5 l/s / 56 cfm
Blows per minute	1450	1350	1200	1250	1200	1620	1620	1140	1400
Piston dia (mm / inch)	48 mm / 1.90"	60.3 mm / 2.40"	57 mm / 2.25"	67 mm / 2.63"	57 mm / 2.25"	-	-	-	-
Piston stroke (mm / inch)	108 mm / 4.25"	140 mm / 5.50"	165 mm / 6.50"	158 mm / 6.25"	165 mm / 6.50"	-	-	-	-
Shank size (mm / inch) - Std	25 x 108 mm / 1" x 4 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"	25 x 108 mm / 1" x 4 1/4"	25 x 108 mm / 1" x 4 1/4"	25 x 108 mm / 1" x 4 1/4"	25 x 108 mm / 1" x 4 1/4"
Shank size (mm / inch) Option - 1	-	28 x 160 mm / 1 1/8" x 6 1/4"	28 x 160 mm / 1 1/8" x 6 1/4"	28 x 160 mm / 1 1/8" x 6 1/4"	28 x 160 mm / 1 1/8" x 6 1/4"	-	-	-	28 x 160 mm / 1 1/8" x 6 1/4"
Shank size (mm / inch) Option - 2	-	-	-	-	-	-	-	-	32 x 160 mm / 1 1/4" x 6 1/4"
Retainer type	Latch	Latch	Spring	Latch	Latch	Latch	Latch	Latch	Latch

Model #	RMT RTEX	RMT P60	RMT 1260	RMT 1260 SVR	RMT 37P	RMT 1290	RMT 1290 SVR	RMT P90
Weight with silencer (kg / lb)	25 kg / 55 lb	33 kg / 73 lb	31 kg / 68 lb	34 kg / 75 lb	37 kg / 81 lb	39 kg / 86 lb	43.5 kg / 96 lb	43 kg / 95 lb
Weight without silencer (kg / lb)	-	31 kg / 68 lb	29 kg / 64 lb	-	-	37 kg / 81 lb	-	41 kg / 90 lb
Length (mm / inch)	780 mm / 31"	690 mm / 27.2"	680 mm / 26.7"	735 mm / 29"	729 mm / 29"	730 mm / 29"	785 mm / 31"	710 mm / 28"
Air pressure (bar / psi)	7 bar / 102 psi	7 bar / 102 psi	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	6 bar / 87 psi	7 bar / 102 psi
Air consumption (l/s / cfm)	18.5 l/s / 39.2 cfm	36 l/s / 76 cfm	34.5 l/s / 73 cfm	34.5 l/s / 73 cfm	35 l/s / 74 cfm	43 l/s / 91 cfm	43 l/s / 91 cfm	40 l/s / 85 cfm
Blows per minute	870	1500	1300	1300	1200	1100	1300	1260
Piston dia (mm / inch)	-	-	-	-	-	-	-	-
Piston stroke (mm / inch)	-	-	-	-	-	-	-	-
Shank size (mm / inch) - Std	32 x 160 mm / 1 1/4" x 6 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"	32 x 160 mm / 1 1/4" x 6 1/4"
Shank size (mm / inch) Option - 1	28 x 160 mm / 1 1/8" x 6 1/4"	28 x 160 mm / 1 1/8" x 6 1/4"	28 x 160 mm / 1 1/8" x 6 1/4"	28 x 160 mm / 1 1/8" x 6 1/4"	-	28 x 160 mm / 1 1/8" x 6 1/4"	28 x 160 mm / 1 1/8" x 6 1/4"	28 x 160 mm / 1 1/8" x 6 1/4"
Shank size (mm / inch) Option - 2	-	-	-	-	-	-	-	-
Retainer type	Latch	Latch	Latch	Latch	Latch	Latch	Latch	Latch

13th Feb 2021 | RMT 500.01.01

All above hammers are available with or without mufflers / silencers , Air Inlet for hammers is 19 mm (3/4") BSP