

RMT 4123 series of chipping hammers are lightweight, compact yet powerful hammers. It has a **pistol-grip handle** with the **self-closing outside trigger**. A simple design ensures easy maintenance and teasing throttlers for precise control. These chipper come with **2", 3" and 4" cylinder option** and also with **bushing choice of "Round" or "Hex"**. Cylinders too are heat treated for longer durability. They are mainly used in Foundries, Fabrication Shops, Mining & Construction applications.



What is good about it?

- Easy maintenance
- Swan neck handle
- Long nozzle for extra life
- Excellent durability
- Available in round and hex shank

Where it is used?


- **In Mining and Construction**
 - Light concrete demolition
 - Roughening concrete surface
 - Scaling and scrubbing concrete and metal surfaces
 - Chip cement adhering to plant and vehicles
- **In Foundry and Forge**
 - Chipping and dressing concrete, caulking, fettling and deflashing, casting & forgings



Lubricator



Working Tools



Spare Parts

Specification

Model #	RMT 4123 2H/2R		RMT 4123 3H/3R		RMT 4123 4H/4R	
Weight	7 kg	15 lb	8 kg	17.65 lb	8.65 kg	17.65 lb
Length	375 mm	14.8"	426 mm	16.75"	460 mm	18.1"
Air pressure	6.2 bar	90 psi	6.2 bar	90 psi	6.2 bar	90 psi
Air consumption	13.6 l/s	29 cfm	14 l/s	30 cfm	14 l/s	30 cfm
Blows per minute	2500		2050		1600	
Piston dia	28.6 mm	1.13"	28.6 mm	1.13"	28.6 mm	1.13"
Piston stroke	50.8 mm	2"	76.2 mm	3"	101.6 mm	4"
Air inlet (BSP thread)	9.5 mm	3/8"	9.5 mm	3/8"	9.5 mm	3/8"
Shank size (Hex)	14.7 mm	0.580"	14.7 mm	0.580"	14.7 mm	0.580"
Shank size (Round)	17.3 mm	0.680"	17.3 mm	0.680"	17.3 mm	0.680"
Retainer type	Spring		Spring		Spring	